

U-Turn Secure Materialist:

MATERIAL NO.	MATERIAL NAME	SPECIFICATION
1	PARATEX RS TX40 CANOPY FABRIC	RIPSTOP NYLON FABRIC - POROSITY : 10-15 CFM - BREAKING STRENGTH : MIN. 25kg - TEARING STRENGTH : MIN. 20kg
2	RADIAL TAPE, UPPER LATERAL BAND	RIBBON NYLON TAPE - WIDTH : 1/2 inch - BREAKING STRENGTH : MIN. 60kg
3	SUSPENSION LINE & VENT LINE	BRAIDED NYLON CORD - BREAKING STRENGTH : MIN. 100kg - ELONGATION : MIN. 20%
4	CENTER LINE	BRAIDED NYLON CORD - BREAKING STRENGTH : MIN. 130kg - ELONGATION : MIN. 20%
5	RISER WEBBING	POLY WEBBING - WIDTH : 27mm - BREAKING STRENGTH : MIN. 2800 KG
6	RISER COVER	NYLON FABRIC - WEIGHT : 6.2 oz/yd ²
7	CANOPY SEWING THREAD	NYLON THREAD N/T 210 D /3 ; YELLOW - BREAKING STRENGTH : MIN. 3.2kg
8	LINES SEWING THREAD	NYLON THREAD - N/T 210 D/ 3 ; BLUE - BREAKING STRENGTH : MIN. 2.4kg
9	RISER SEWING THREAD	NYLON THREAD - P/T 1260 D/ 3 ; BLACK - BREAKING STRENGTH : MIN. 18.5kg